


Tizen.IoTivity.Sensoring

w/ Analog Sensor

소프트웨어센터 | 소프트웨어 플랫폼 팀 | 박정훈

2017. 10. 26


SOSCON
SAMSUNG
OPEN SOURCE
CONFERENCE




Analog Sound Sensor (DFR0034)

Specification

- Supply Voltage: 3.3V to 5V
- Detects the sound intensity
- **Interface: Analog**
- Size: 22x30mm






GND
VCC
Analog signal output



Raspberry Pi 3 GPIO Header


Pin#	NAME	NAME	Pin#
01	3.3v DC Power	DC Power 5v	02
03	GPIO02 (SDA1 , I ² C)	DC Power 5v	04
05	GPIO03 (SCL1 , I ² C)	Ground	06
07	GPIO04 (GPIO_GCLK)	(TXD0) GPIO14	08
09	Ground	(RXD0) GPIO15	10
11	GPIO17 (GPIO_GEN0)	(GPIO_GEN1) GPIO18	12
13	GPIO27 (GPIO_GEN2)	Ground	14
15	GPIO22 (GPIO_GEN3)	(GPIO_GEN4) GPIO23	16
17	3.3v DC Power	(GPIO_GEN5) GPIO24	18
19	GPIO10 (SPI_MOSI)	Ground	20
21	GPIO09 (SPI_MISO)	(GPIO_GEN6) GPIO25	22
23	GPIO11 (SPI_CLK)	(SPI_CE0_N) GPIO08	24
25	Ground	(SPI_CE1_N) GPIO07	26
27	ID_SD (I ² C ID EEPROM)	(I ² C ID EEPROM) ID_SC	28
29	GPIO05	Ground	30
31	GPIO06	GPIO12	32
33	GPIO13	Ground	34
35	GPIO19	GPIO16	36
37	GPIO26	GPIO20	38
39	Ground	GPIO21	40




MCP3008 Features

- **10-bit resolution** (0 ~ 1023)
- **8 input channels**
- Analog inputs programmable as single-ended or pseudo-differential pairs
- On-chip sample and hold
- **SPI serial interface**
- Single supply operation: 2.7V - 5.5V
- Industrial temp range: -40°C to +85°C


RPi 3




SPI 연결 케이블




빵판 + MCP3008




sound sensor





점프 케이블





How to connect A/D Converter and RPi





How to connect analog sound sensor





Set duration for reading sensor values

in [controller.c](#)

```
static bool service_app_create(void *data)
{
    ...
    ad->getter_timer = ecore_timer_add(0.01f , control_sensors_cb, ad);
    ...
    ...
    return true;
}
```

Read sensor values in timer callback function

in [controller.c](#)

```
static Eina_Bool control_sensors_cb(void *data)
{
    unsigned int sl_value = 0;
    ...
    resource_read_sound_level_sensor( 0 , &sl_value);
    ...
    return ECORE_CALLBACK_RENEW;
}
```

※ 참고

https://git.tizen.org/cgit/apps/native/position-finder-server/plain/src/resource/resource_adc_mcp3008.c

https://git.tizen.org/cgit/apps/native/position-finder-server/plain/inc/resource/resource_sound_level_sensor.h


https://git.tizen.org/cgit/apps/native/position-finder-server/plain/src/resource/resource_sound_level_sensor.c

Check the sensor values

Run the project on RPi3

Run > Run As > ...

Open a shell



See logs

Execute *dlogutil* in the opened shell.

```
$ dlogutil TT
```

THANK YOU

SOSCON
SAMSUNG
OPEN SOURCE
CONFERENCE

